



**Prevista Dry WC element
adjustable ceramic height
with shower WC connection
1120 mm**

- in addition optional available Prevista Dry Support set model 8570.37
- for pre-wall mounting please order separately: Prevista Dry Fixing set model 8570.36
- compatible with all WC flush plates for Prevista, integration in Prevista Dry Plus, variably-adjustable ceramic height, dual flush technology, barrier-free

Components

powder-coated frame (40x40), concealed cistern 3H, condensate insulation for concealed cistern halogen-free according to DGNB ENV1.2 Criterion QS4 compliant, flushing throttle, conduit pipe for shower WC connection, WC connection fitting, fixing material, lockable foot for adjusting the construction height, water connection R $\frac{1}{2}$ at the back and top, WC connection elbow DN90 (depth-adjustable) made of PP, eccentric adapter DN90/100 made of PP

Note

Flush plates and accessories: WC and urinal flush plates for Prevista product group.

Model 8521

Article 771 997

Properties

Partial flush volume factory setting	partial flush volume factory setting	approx. 3 l
Partial flush volume setting range	partial flush volume setting range	approx. 2–4 l
Large flush volume setting range	approx. 3.5–7.5 l	
Max.load	Max. load	400 kg
Max. projection	700 mm	
Construction height	CH	1120
Width	B	500
Height adjustable	HA	330–390 mm
Weight	13500 g	

Data sheet



**Prevista Dry WC element
adjustable ceramic height
with shower WC connection
1120 mm
Model 8521
Article 771 997**

Properties

Volume	82547.322 cm ³
Material	steel, PE