

CF 160



FROGTAPE® BRAND DELICATE SURFACE PAINTER'S TAPE



TYPICAL APPLICATIONS

- For interior use on finished wood, freshly painted walls and trim (24 hours old), coated wallpaper, laminate, vinyl, primed wall board, cabinets and floors

PRODUCT FEATURES

- Low adhesion, solvent-free adhesive system
- Exclusive PaintBlock® Technology
- Prevents paint bleed to deliver very sharp lines
- 60-day clean removal from indoor surfaces

CONSTRUCTION

Overall Grade/Function: Delicate surface

Backing: Washi paper

Adhesive: Synthetic rubber-based adhesive

STANDARD WIDTH(S)

24 mm 36 mm 48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment.

Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

Shurtape

TECHNOLOGIES

COLOR(S)



| PHYSICAL PROPERTIES | STANDARD | METRIC |
|-----------------------------|-----------------|--------------|
| Tensile Strength | 19 lbs/in width | 33.3 N/10 mm |
| Adhesion to Stainless Steel | 25 oz/in width | 2.74 N/10 mm |
| Thickness | 3.3 mils | 0.08 mm |
| Elongation | 5.0% | 5.0% |

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

*Test before use on all surfaces and when using solvent-based coatings; FrogTape® was designed for use when applying latex paint; May not be compatible with all floor surfaces - consult floor manufacturer for guidance.

