

ZIP-FIX[®]

CAVITY FIXING

RAPID INSTALLATION

Heavy duty cavity wall anchor for use in **plasterboards**, most **hollow concrete blocks**, **cavity walls** and **ceilings**.

Pack includes both **40mm** and **60mm** screws for a wider variety of fixture thicknesses.

PERFECT FOR FITTING



TV Brackets



Radiators



Cabinets

WEIGHTS & MATERIALS



30 KG
DRYWALL / PLASTERBOARD
12.5mm Thickness



47 KG
DOUBLE BOARD
25mm Thickness



56 KG
DENSE BOARD
15mm Thickness



Up To 60 KG
HOLLOW BLOCK

TECHNICAL DATA

Substrate	Plasterboard 12.5mm Thickness	25mm Double Board	15mm Dense Board	Block
Thread Ø (mm)	M6	M6	M6	M6
Drill Hole Ø (mm)	13	13	13	13
Rec. Tensile Load (kN)	0.30	0.47	0.56	0.60
Max Rec. Load (kg)	30	47	56	60

Product Code	Screw Lengths (mm)	Thread Ø (mm)	FCH Ø (mm)	MFT (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
--------------	--------------------	---------------	------------	----------	----------------	--------------------	--------------------

BOX

ZIP650	40 and 60	M6	6	45	50	8	192
--------	-----------	----	---	----	----	---	-----

BAG

ZIP6	40 and 60	M6	6	45	10	42	1260
------	-----------	----	---	----	----	----	------

FCH = FIXTURE CLEARANCE HOLE. MFT = MAX. FIXTURE THICKNESS



Drill a 13mm hole in the substrate. 50mm cavity clearance required behind substrate.



Ensuring the thumb tab faces upwards, insert the metal toggle through the hole, so it pivots down behind the substrate.



Zip the nylon collar towards the wall so the collar sits into the drilled hole. Then snap off the nylon arms.



Insert a M6 screw through the fixture and into the threaded part of Zip-Fix and tighten until secure.