

## **S910**

1/4" and 1/2" Square Drive Socket and Deep Socket Set with Metric Hex Profile and Combination Spanner Set



## PRODUCT DETAILS

- 12-Piece 1/4" hex sockets 4, 4.5, 5, 5.5, 6, 7, 8,
- 9, 10, 11, 12 and 13 mm
- 10 1/4" hex deep sockets 4, 5, 6, 7, 8, 9, 10, 11, 12 and 13 mm
- 13-Piece 1/2" hex sockets 10, 11, 12, 13, 14, 15, 17, 19, 22, 24, 27, 30 and 32 mm
- $\bullet$  Two 1/4" extension bars, 50 mm/2" and 100 mm/4"
- One 1/4" sliding T-bar
- One 1/4" universal joint
- One 1/4" bit holder
- One 1/4" bit adaptor
- One 1/4" spinner with two-component handle
- One 1/4" magnetic adaptor
- $\bullet$  Five 1/4" Phillips bits, PH0, PH1, PH2, PH3 and PH4
- Three 1/4" slotted bits: 4, 5.5 and 7 mm
- Three 1/4" Pozidriv bits: PZ1, PZ2 and PZ3
- Six 1/4" hex bits, 3, 4, 5, 6, 8 and 10 mm
- Eight 1/4" TORX® bits, T8, T10, T15, T20, T25, T27, T30 and T40
- Three 5/16" TORX® bits: T45, T50 and T55
- Two 1/2" extension bars, 5" and 10"

- One 1/2" universal joint
- One 1/2" spark plug hex socket, 21 mm (13/16")
- One 1/2" x 5/16" bit holder
- One 1/2" T-adaptor
- Three hexagon L-keys: 1.5, 2 and 2.5 mm
- One 1/4" ratchet, quick release, 60 teeth/6° action angle
- One 1/2" ratchet, quick release, 60 teeth/6° action angle
- Four flex head wrenches, 8-9, 10-11, 12-13 and 14-15 mm
- Six combination spanners: 8, 10, 12, 13, 14 and
- 17 mm on a practical removable tool-rack
- One removable three-section plastic box with lid
- Matte finish
- High-performance alloy steel
- Less wear and damage to fastener thanks to Dynamic-Drive™ profile sockets
- Quick socket release button on ratchet
- Case: High density polythene (HDPE)
- Standards: ISO 1174 and DIN 3120



## PRODUCT ATTRIBUTES

Product		$\bigcirc$		g
S910	375 mm	320 mm	110 mm	6880 g



Follow the Fish!