| CI/Sfb | (52.6) | I In6    | ř |
|--------|--------|----------|---|
|        | Februa | ary 2018 |   |



## DC1-BL-BO and DC1-GR-BO Drain Connector with Boss Connection



Installation Instructions for the DC1-BL-BO / DC1-GR-BO 4" / 110mm pipe to BS 4514 and 1.5" universal pipe boss with blank cap.

- These Boss Connectors have been designed for low level connections from a WHB, bath, shower tray or stub stack Installation where the invert level is no ore than 1.3m to the invert level of the underground drainage.
- The Boss Connector should only be installed in single storey properties at floor level.
- These Boss Connector should not be installed in two storey or high rise installations.

4"/110mm x 4"/110mm Connector with 'O' seal socket to fit 4"/110mm pipe to BS 4514 and 1½" universal pipe boss including blanking cap 4"/110mm x 4"/110mm Connector with 'O' seal so cket to fit 4"/110mm pipe to BS 4514 and 1½" universal pipe boss including blanking cap

Code (Black)

DC1-BL-BO

Code (Grey)

DC1-GR-BO

McAlpine & Co Ltd., Kelvin Avenue, Hillington, Glasgow G52 4LF Tel: 0141 882 3213 Fax: 0141 891 5065 Fax (Sales Office) 0141 883 5697

## www.mcalpineplumbing.com