



ANTI CROSS-FLOW AND RODENT BARRIER VALVE





McALPINE & CO. LTD., Kelvin Avenue, Hillington, Glasgow G52 4LF. Telephone: 0141-882 3213 Fax: 0141-891 5065 Fax: Orders (Sales Office) 0141-883 5697 Website: www.mcalpineplumbing.com

L-WC-CON

© McAlpine & Co. Ltd. July 2016

Flexible WC Connectors

- All inlet seals will fit 97-107mm diameter
- Minici scals with it >>10/hith clained pan spigot.
 WC-F18R : WC-F23R : WC-F26R : WC-F23RV : WC-F26RV : WC-CON8F and WC-CON8FV fit inside 4"/110mm diameter pipe
- WC-F18S : WC-F23S : WC-F26S : WC-F23SV and WC-F26SV fit inside 31/2"/90mm diameter pipe.
- Connectors with a plain end have an outside diameter of 110mm.
- All Connectors with 1¹/₄" Universal Boss include Blank Cap with 11/2" BSP Thread.
- Installations requiring an extended straight length should be supported firmly to prevent
- any sagging. Do not attempt to dear blockages with the use
- of drain rods. WHEN INSTALLING THE WC CONNECTOR TO THE WC PAN SPIGOT WE RECOMMEND THAT THE INLET SOCKET OF THE CONNECTOR BE LUBRICATED WITH CLEAN WATER THEN PUSHED FIRMLY ON TO THE SPIGOT OF THE WC PAN. THE SOIL PIPE TO BE CONNECTED TO THE CONNECTOR OUTLET SHOULD BE CUT SQUARE AND FREE OF ANY DEBRIS. THE FINNED SEAL SPIGOT OUTLET OF THE WC CONNECTOR MAY BE LUBRICATED WITH SILICONE GREASE TO AID ISTALLATION INTO THE INTERNAL DIAMETER OF THE SOIL PIPE.
- Do not over extend or pull flex off inlet and outlet locations. Extend flex by pulling from the middle of the flex and not from the fixture locations.





- Do not over extend or pull over the recommended length.
- Installations requiring an extended straight length should be supported.
- Ensure all joints are secure before final fix of the WC pan.
- Do not attempt to clear blockages with the use of drain rods.



Keep sharp tools and abrasive materials away from flexible pipe.

WHEN INSTALLING THE WC CONNECTOR TO THE WC PAN SPIGOT WE RECOMMEND THAT THE INLET SOCKET OF THE CONNECTOR BE LUBRICATED WITH CLEAN WATER THEN PUSHED FIRMLY ON TO THE SPIGOT OF THE WC PAN. THE SOIL PIPE TO BE CONNECTED TO THE CONNECTOR OUTLET

LO BE CONVECTOR TO THE CONVECTOR OUTLET LO BE CUT SQUARE AND FREE OF ANY DEBRIS. THE 2D SEAL SPIGOT OUTLET OF THE WC CONNECTOR MAY B IC ATED WITH SILICONE GREASE TO AID IN STALLATION THE INTERNAL DIAMETER OF THE SOL PIPE.

- We would recommend the use of a Flexible Hose Clip Driver as illustrated to tighten the jubilee clip. (Standard 7mm driver for hose clips as shown).
- Please note: When these products are used on excessively misshapen pan outlet spigots, the use of silicone sealant can be an advantage to ensure an air and water tight seal is achieved.



and MACFIT Connectors

G INSTRUCTION 2 DIMENSIONAL LEAFLE



Code: WC-CON8FV

220mm - 400mm

- Tested to BS5627.
- pan spigot.
- · Connectors with a plain end have an outside diameter of 110mm.
- **Rigid WC Connectors** Straight. Adjustable Length All inlet seals will fit 97-107mm diameter Code: WC-CON3 205m All outlet seals will fit inside 4"/110mm diameter pipe except WC-CON2B, WC-CON5B, WC-CON7B, WC-EXTB and WC-EXTD which fit inside 31/2" /90mm 20mm Offset. diameter pipe. Code: WC-CON4 WHEN INSTALLING THE WC CONNECTOR TO THE WC PAN SPIG OT WE RECOMMEND THAT THE INLET SOCKET OF THE CONNECTOR BE LUBRICATED WITH CLEAN WATER THEN PUSHED FIRMLY ON TO THE SPIGOT OF THE WC PAN. THE SOIL PIPE TO BE 40mm Offset CON NECTED TO THE CON NECTOR OUTLET SHOULD BE CUT SOUARE AND FREE OF ANY DEBRIS. THE FINNED SEAL SPIGOT OUTLET OF THE WC CONNECTOR MAY BE LUBRICATED WITH SILICONE GREASE TO AID ISTALLATION INTO THE INTERNAL Code: WC-CON4A DIAMETER OF THE SOIL PIPE. Straight. 40mm Offset. Code: WC-CON1 Straight, 11/4" Universal 181 Code: WC-CON4B Pipe Boss, including Blanking Cap with 11/2" BSP Thread. 20mm Offset. Code: WC-CON1V Adjustable Length. Straight. 2000 Adjustable Length Code: WC-CON5 Code: WC-CON2 24mm Offset Reducer. raight Reducer. Adjustable Length. djustable Length. 2000 Code: WC-CON2B Code: WC-CON5B MACFIT 90° Space Saving Bend. Adjustable Length. (patent pending) WC Connectors 28mm Manufactured in EVA Code: WC-CONQP Tested to BS 5627 : 1984 · Inlet seals will fit Pans manufactured to BS 5503/4 and BS 1213. 45° Angle. Outlet seals will fit inside 4" /110mm diameter pipe except MAC-EXTB which fits inside 31/2"/90mm pipe and MAC-EXTC which fits inside 3"/75mm pipe. Code: WC-CON16 WHEN INSTALLING THE WC CONNECTOR TO THE WC PAN SPIGOT WE RECOMMEND THAT THE INLET SOCKET OF THE CONNECTOR BE LUBRICATED WITH CLEAN WATER THEN PUSHED FIRMLY ON TO THE Straight Extension. SPIGOT OF THE WC PAN. THE SOIL PIPE TO BE CONNECTED TO THE CONNECTOR OUTLET SHOULD BE CUT SQUARE AND FREE OF ANY DEBRIS. THE Adjustable Length. FINNED SEAL SPIGOT OUTLET OF THE WC CONNECTOR MAY BE LUBRIC ATED WITH SILIC ONE Code: WC-EXTA GREASE TO AID ISTALLATION INTO THE INTERNAL DIAMETER OF THE SOIL PIPE. Straight. Straight Extension Reduce 4"/110mm Outlet.

25mm

25mm

Code: MAC-1

Code: MAC-3

Code: MAC-4

31/2"/90mm Outlet.

20mm Offset.

4"/110mm Outlet.

Straight.



Y	170mm	11111
-	170000	•

St
_















- Adjustable Length.
- Code: WC-EXTB
- 10mm Offset Extension Adjustable Length.
- Code: WC-EXTC
- 10mm Offset Extension Reduce Adjustable Length.
- Code: WC-EXTD



10mm Offset

90° Bend, 11/4" Universal